


Non-standard "Hoof-print" linetype detail.



Note A: The proposed linetype to be located at mid distance between bridge parapet (narrowest point at palister) and the inner edge of the shared use path margin line.


Note B: The proposed linetype to be located at mid distance between the rear of footpath and the inner edge of the shared use path margin line.


Dimension "Y" is to be the same as Dimension "X". Dimension "X" is the distance between the crossing studs and the cycle tactile paving.


The shared use area around the Toucan must not have hoofprint markings.

Setting out to be agreed with the engineer on site.

 Route of hoof-print lining.

 Extents of Shared Use area

 Line to Diagram 1057 (750mm x 1215mm))

 Line to Diagram 1058.1 (705mm and 1035mm as noted)

	INITIAL	REV	AMENDMENTS	DATE
DRAWN BY	MRM			
CHECKED BY	GT			
SCALE	1:200	A1		
DATE	OCT 2010			

Orbital Cycle Route: Crichton Avenue  
Proposed Hoofprint markings

BASED UPON THE ORDINANCE SURVEY MAPPING WITH THE PERMISSION OF THE CONTROLLER OF HER MAJESTY'S STATIONERY OFFICE. © CROWN COPYRIGHT. UNAUTHORISED REPRODUCTION INFRINGES CROWN COPYRIGHT AND MAY LEAD TO PROSECUTION OR CIVIL PROCEEDINGS.  
City of York Council, Licence No. 1000 20818

DEC08010331